

More Precision

Eltrotec // Industrial Endoscopes



Camera-monitor system for mobile use

ELTROTEC Analog Color Camera - CUBECAM PRO

- Upgrading rigid and flexible endoscopes to video endoscopes
- Use only with the ELTROTEC iCapture Monitor

Documentation Unit

Model

Inversion

Text comments

ELTROTEC iCapture Monitor

 Upgrading rigid and flexible endoscopes to video endoscopes Use only with analog "CUBECAM PRO" color CCD cameras


Model	CUBECAM PRO
Part number	20702312
Image sensor	1/3" CCD
Resolution	752 x 582 pixels
Horizontal resolution	>480 lines
Color	Bayer pattern
Shutter speed	auto (1/50 s to 1/10,000 s)
Images per second	50
White balance	automatic
Lens connection	C-Mount
Interface	Video output 5-pin
Power supply	12 VDC (via iCapture Monitor)
Dimensions (L x W x D)	47mm x 47mm x 55mm
Weight	85 g
Operating temperature	0 °C to +50 °C
Storage temperature	-20 °C to +60 °C
Connection cables	L 1800 mm











Eltrotec iCapture Monitor

horizontal and vertical image inversion, controls for brightness,

contrast and color

integrated text-overlay generator for text lines with up to 32 characters



Sensors and Systems from Micro-Epsilon



Sensors and systems for displacement, distance and position



Sensors and measurement devices for non-contact temperature measurement



Measuring and inspection systems for metal strips, plastics and rubber



Optical micrometers and fiber optics, measuring and test amplifiers



Color recognition sensors, LED analyzers and inline color spectrometers



Industrial endoscopes, light sources